

ALLIS-CHALMERS

LIFT TRUCK SPECIFICATIONS

| TRUCK MODEL COMPARTMENT | VOLT- AGE | AMPS | BATTERY TYPE | DIMENSIONS | | | CHARGER | CHARGER |
|--|--------------|------|-----------------|------------|-------|-------|-----------|-----------|
| | | | | X | Y | Z | (1) PHASE | (3) PHASE |
| ACE100/100A/100CR 39.75 x 35.13 x 23.50 | 36 | 1190 | 18-85-29 | 38.50 | 33.63 | 22.63 | N/A | 18-1200C |
| | 48 | 850 | 24-85-21 | 38.50 | 33.00 | 22.63 | N/A | 24-875C |

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|---|----|------|----------|-------|-------|-------|-----|----------|
| ACE100HD/120HD 48.50 x 39.50 x 25.00 | 36 | 1360 | 18-85-33 | 38.50 | 38.13 | 23.25 | N/A | 18-1450C |
| | 48 | 1105 | 24-85-27 | 42.00 | 38.50 | 23.25 | N/A | 24-1050C |
| | 48 | 1190 | 24-85-29 | 45.00 | 38.50 | 23.25 | N/A | 24-1200C |

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/COVER

| | | | | | | | | |
|---|----|------|----------|-------|-------|-------|---------|----------|
| ACE120/120A/120CR 39.75 x 40.63 x 23.50 | 36 | 1360 | 18-85-33 | 38.50 | 38.13 | 22.63 | N/A | 18-1450C |
| | 48 | 1020 | 24-85-25 | 39.00 | 38.50 | 22.63 | N/A | 24-1050C |
| ACE20A/25/25A/30/30A ACE20/25/30/200 CR 32.50 x 26.25 x 23.50 | 36 | 595 | 18-85-15 | 31.75 | 24.00 | 22.63 | 18-600B | 18-600C |
| | 48 | 510 | 24-85-13 | 31.00 | 25.75 | 22.63 | 24-450B | 24-450C |
| ACE35/40/45/50 38.75 x 28.00 x 23.50 | 36 | 935 | 18-85-23 | 38.50 | 26.75 | 22.63 | N/A | 18-875C |
| | 48 | 680 | 24-85-17 | 38.50 | 27.00 | 22.63 | N/A | 24-725C |
| ACE55 38.75 x 32.00 x 23.50 | 36 | 1020 | 18-85-25 | 38.50 | 29.13 | 22.63 | N/A | 18-1050C |
| | 48 | 765 | 24-85-19 | 38.50 | 29.75 | 22.63 | N/A | 24-725C |
| ACE60/60A/60CR ACE70/70A/70CR 41.00 x 32.50 x 23.50 | 36 | 1105 | 18-85-27 | 38.50 | 31.38 | 22.63 | N/A | 18-1050C |
| | 48 | 765 | 24-85-19 | 38.50 | 29.75 | 22.63 | N/A | 24-725C |

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

ALLIS-CHALMERS

LIFT TRUCK SPECIFICATIONS

| TRUCK MODEL COMPARTMENT | VOLT- AGE | AMPS | BATTERY TYPE | DIMENSIONS | | | CHARGER | CHARGER |
|--|--------------|------|-----------------|------------|-------|-------|-----------|-----------|
| | | | | X | Y | Z | (1) PHASE | (3) PHASE |
| ACE60HD/80HD 40.50 x 39.50 x 23.13 | 36 | 1360 | 18-85-33 | 38.50 | 38.13 | 22.63 | N/A | 18-1450C |
| | 48 | 1020 | 24-85-25 | 39.00 | 38.50 | 22.63 | N/A | 24-1050C |
| ACE80/80A/80CR 41.00 x 35.50 x 23.50 | 36 | 1190 | 18-85-29 | 38.50 | 34.00 | 22.63 | N/A | 18-1200C |
| | 48 | 850 | 24-85-21 | 38.50 | 33.00 | 22.63 | N/A | 24-875C |
| ACET 38.88 x 26.00 x 20.00 | 36 | 550 | 18-55-21 | 38.50 | 24.63 | 19.25 | 18-600B | 18-600C |
| ACET20A/25A/30/30A 38.88 x 26.25 x 20.00 | 36 | 550 | 18-55-21 | 38.50 | 24.63 | 19.25 | 18-600B | 18-600C |
| | 36 | 495 | 18-55-19 | 37.00 | 25.63 | 19.25 | 18-450B | 18-450C |
| ACET40/40A/45A/50/50A 38.88 x 27.62 x 20.00 | 36 | 605 | 18-55-23 | 38.50 | 27.00 | 19.25 | 18-600B | 18-600C |
| ACET55A 38.88 x 31.62 x 20.00 | 36 | 715 | 18-55-27 | 38.50 | 31.50 | 18.50 | 18-725B | 18-725C |

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|---|----|------|-----------|-------|-------|-------|---------|----------|
| ACNR30L/40L ACNS30L/40L 38.50 x 16.63 x 32.25 | 36 | 750 | 18-125-13 | 38.00 | 15.50 | 30.38 | 18-725B | 18-725C |
| ACNR30S/40S ACNS30S/40S 38.50 x 15.00 x 32.25 | 24 | 875 | 12-125-15 | 35.25 | 13.00 | 30.38 | 12-875B | 12-875C |
| | 24 | 1000 | 12-125-17 | 38.25 | 13.50 | 30.38 | N/A | 12-1050C |
| | 24 | 850 | 12-170-11 | 35.38 | 13.13 | 30.38 | 12-875B | 12-875C |

ABOVE REQUIRES: 350 RED CONN., POSITION-B, 14" LEAD LENGTH, W/O COVER

ALLIS-CHALMERS

LIFT TRUCK SPECIFICATIONS

| TRUCK MODEL COMPARTMENT | VOLT- AGE | AMPS | BATTERY TYPE | DIMENSIONS | | | CHARGER | CHARGER |
|--------------------------------------|--------------|------|-----------------|------------|-------|-------|-----------|-----------|
| | | | | X | Y | Z | (1) PHASE | (3) PHASE |
| ACOP15S/30C 38.50 x 14.50 x 31.50 | 24 | 750 | 12-125-13 | 35.88 | 11.75 | 30.38 | 12-725B | 12-725C |
| | 24 | 1000 | 12-125-17 | 38.25 | 13.50 | 30.38 | N/A | 12-1050C |
| | 24 | 850 | 12-170-11 | 35.38 | 13.13 | 30.38 | 12-875B | 12-875C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|-----------------------------------|----|------|-----------|-------|-------|-------|-----|----------|
| ACOP25SL 36.38 x 15.63 x 31.25 | 24 | 1020 | 12-170-13 | 35.38 | 15.50 | 30.38 | N/A | 12-1050C |
|-----------------------------------|----|------|-----------|-------|-------|-------|-----|----------|

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|---|----|-----|----------|-------|-------|-------|---------|---------|
| ACWA40/60 ACWB40/60 ACWF40/60 31.75 x 8.12 x 23.50 | 12 | 510 | 6-85-13 | 30.88 | 7.75 | 23.25 | 6-450B | 6-450C |
| OPTIONAL COMP. 31.75 x 13.38 x 23.50 | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-450B | 12-450C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

| | | | | | | | | |
|------------------------------------|----|------|----------|-------|-------|-------|---------|----------|
| E30 39.25 x 26.25 x 23.50 | 36 | 850 | 18-85-21 | 38.50 | 24.50 | 22.63 | N/A | 18-875C |
| | 48 | 595 | 24-85-15 | 38.50 | 24.00 | 22.63 | 24-600B | 24-600C |
| E40/E50S 39.25 x 28.25 x 23.50 | 36 | 935 | 18-85-23 | 38.50 | 26.75 | 22.63 | N/A | 18-875C |
| | 48 | 680 | 24-85-17 | 38.50 | 27.00 | 22.63 | N/A | 24-725C |
| E40L/E60S 29.25 x 31.25 x 23.50 | 36 | 1020 | 18-85-25 | 38.50 | 29.13 | 22.63 | N/A | 18-1050C |
| | 48 | 765 | 24-85-19 | 38.50 | 29.75 | 22.63 | N/A | 24-725C |

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

ALLIS-CHALMERS

LIFT TRUCK SPECIFICATIONS

| TRUCK MODEL COMPARTMENT | VOLT- AGE | AMPS | BATTERY TYPE | DIMENSIONS | | | CHARGER | CHARGER |
|------------------------------------|--------------|------|-----------------|------------|-------|-------|-----------|-----------|
| | | | | X | Y | Z | (1) PHASE | (3) PHASE |
| E50L, E60 39.25 x 34.25 x 23.50 | 36 | 1105 | 18-85-27 | 38.50 | 31.38 | 22.63 | N/A | 18-1050C |
| | 36 | 1190 | 18-85-29 | 38.50 | 33.63 | 22.63 | N/A | 18-1200C |
| | 48 | 850 | 24-85-21 | 38.50 | 33.00 | 22.63 | N/A | 24-875C |

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|----------------------------------|----|------|----------|-------|-------|-------|-----|----------|
| ET25/30 38.75 x 21.50 x 23.00 | 24 | 1105 | 12-85-27 | 38.38 | 21.06 | 22.63 | N/A | 12-1200C |
|----------------------------------|----|------|----------|-------|-------|-------|-----|----------|

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|---|----|-----|----------|-------|-------|-------|---------|---------|
| ET700/HWR20 33.00 x 8.50 x 23.25 | 12 | 510 | 6-85-13 | 30.88 | 7.75 | 23.25 | 6-450B | 6-450C |
| OPTIONAL COMP. 33.00 x 13.38 x 23.25 | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-450B | 12-450C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

| | | | | | | | | |
|--|----|-----|----------|-------|-------|-------|---------|---------|
| HWC20 31.75 x 13.38 x 23.25 | 12 | 510 | 6-85-13 | 30.88 | 7.75 | 23.25 | 6-450B | 6-450C |
| | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-450B | 12-450C |
| HWC30 HWS20/30/40 31.75 x 8.12 x 23.50 | 12 | 510 | 6-85-13 | 30.88 | 7.75 | 23.25 | 6-600B | 6-600C |
| OPTIONAL HWC30 31.75 x 13.38 x 23.25 | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-600B | 12-600C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

ALLIS-CHALMERS

LIFT TRUCK SPECIFICATIONS

| TRUCK MODEL COMPARTMENT | VOLT- AGE | AMPS | BATTERY TYPE | DIMENSIONS | | | CHARGER | CHARGER |
|--------------------------------|--------------|------|-----------------|------------|-------|-------|-----------|-----------|
| | | | | X | Y | Z | (1) PHASE | (3) PHASE |
| HWR40 33.00 x 13.38 x 23.25 | 12 | 1020 | 6-85-25 | 29.38 | 13.00 | 23.25 | N/A | 6-1050C |
| | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-450B | 12-450C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

| | | | | | | | | |
|--|----|------|----------|-------|-------|-------|-----------|---------|
| LWA45/60, LWB45/60, LWF45/30/60, LWP45/30/60 33.00 x 8.12 x 23.50 | 12 | 510 | 6-85-13 | 30.88 | 7.75 | 23.25 | 6-450B | 6-450C |
| | 24 | 170 | 12-85-5 | 24.75 | 6.63 | 23.25 | 12-180A/B | N/A |
| OPTIONAL COMP. LWA45/60, LWB45/60, LWP45/60 33.00 x 14.50 x 23.50 | 12 | 1020 | 6-85-25 | 29.38 | 13.00 | 23.25 | N/A | 6-1050C |
| | 24 | 510 | 12-85-13 | 30.63 | 12.88 | 23.25 | 12-450B | 12-450C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

| | | | | | | | | |
|--|----|------|-----------|-------|-------|-------|---------|----------|
| SC14/25/30/40 38.25 x 16.63 x 31.50 | 24 | 875 | 12-125-15 | 35.25 | 13.00 | 30.38 | 12-875B | 12-875C |
| | 24 | 1020 | 12-170-13 | 35.38 | 15.50 | 30.38 | N/A | 12-1050C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

| | | | | | | | | |
|---|----|-----|-----------|-------|-------|-------|---------|---------|
| SR20/30 SS30/40 38.25 x 12.13 x 31.50 | 24 | 750 | 12-125-13 | 35.88 | 11.75 | 30.38 | 12-725B | 12-725C |
| | 24 | 600 | 12-150-9 | 35.38 | 10.88 | 30.38 | 12-600B | 12-600C |

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

Jun-98