

BARRETT

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
GS4/4X	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
GMG24A/X/SB 31.5 x 13.38 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
OPTIONAL COMP. 38.00 x 13.38 x 31.00	24	700	12-100-15	35.38	12.88	26.25	12-725B	12-725C
	24	875	12-125-15	35.25	13.00	31.00	N/A	12-875C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 31" LEAD LENGTH, W/COVER

HPG40/60	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
HPG/DP	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
32.00 x 8.13 x OPEN	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 32.00 x 13.25 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

ORDER SELECTORS								
RCOS/RCSS	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
32.50 x 13.38 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 25" LEAD LENGTH, W/COVER

STAND UP RIDERS, NARROW AISLE, NARROW AISLE REACH TRUCK								
RET20/25/30/SS	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
RPG40/60 RST30/40 32.00 x 13.25 x 31.00		750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 25" LEAD LENGTH, W/COVER

BARRETT TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
STAND UP RIDERS, NARROW AISLE, NARROW AISLE REACH TRUCK								
RRT40/DR	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
RRT130/134/140	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
RST140/150 38.75 x 14.50 x 32.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL COMP.	36	600	18-100-13	38.00	15.50	26.25	18-600B	18-600C
38.75 x 16.50 x 32.00	36	750	18-125-13	38.00	15.50	31.00	18-725B	18-725C
38.75 x 21.25 x 32.00	36	1000	18-125-17	38.50	20.13	31.00	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/O COVER

STAND UP RIDERS, NARROW AISLE, NARROW AISLE REACH TRUCK								
RSSS15	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
32.50 x 13.25 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 25" LEAD LENGTH, W/COVER

WALKIE, RIDER/WALKIE, TOW TRACTORS								
DG24								
31.75 x 13.25 x 23.50	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

WALKIE, RIDER/WALKIE, TOW TRACTORS								
PG-PGK40/60/80	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
PGX-HSC40/60/80	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
32.00 x 8.13 x OPEN	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP.	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
32.00 x 13.25 x OPEN	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

BARRETT TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE, RIDER/WALKIE, TOW TRACTORS								
PXG-HS 29.00 x 13.25 x OPEN	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
SG12 31.50 x 8.13 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
SG24/R/RF SHG24/24F/24R/24RF 31.50 x 13.25 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
STG40/60 32.00 x 8.13 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 32.00 x 13.25 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
WALKIE, RIDER/WALKIE, TOW TRACTORS								
SGX-1-40/60/80 32.00 x 8.13 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
OPTIONAL COMP. 27.13 x 13.00 x OPEN	24	425	12-85-11	26.38	12.88	23.25	12-450B	12-450C
	24	500	12-100-11	26.38	12.75	26.25	12-450B	12-450C
	24	625	12-125-11	26.38	12.88	31.00	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

BARRETT TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
TTG10/15 32.00 x 8.13 x OPEN OR TTG20/25 32.00 x 10.13 x OPEN	12 12 12	510 600 750	6-85-13 6-100-13 6-125-13	30.88 30.88 30.88	7.75 7.75 7.75	23.25 26.25 31.00	6-450B 6-600B 6-725B	6-450C 6-600C 6-725C
OPTIONAL COMP. 32.00 x 16.63 x OPEN	24 24 24	510 600 750	12-85-13 12-100-13 12-125-13	30.63 30.88 30.88	12.88 12.88 12.88	23.25 26.25 31.00	12-450B 12-600B 12-725B	12-450C 12-600C 12-725C
TTG30 32.00 x 16.63 x OPEN	12 12	765 935	6-85-19 6-85-23	31.25 27.13	13.13 13.00	23.25 23.25	6-725B N/A	6-725C 6-1050C
TTG40 32.00 x 22.63 x OPEN	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
OPTIONAL COMP. FOR ALL TTG MODELS 32.00 x 16.63 x OPEN	24 24 24	510 600 750	12-85-13 12-100-13 12-125-13	30.63 30.88 30.88	12.88 12.88 12.88	23.25 26.25 31.00	12-450B 12-600B 12-725B	12-450C 12-600C 12-725C
WALKIE, RIDER/WALKIE, TOW TRACTORS								
WP40/60/80 WRP40 32.00 x 8.25 x OPEN	12 12 12	510 600 750	6-85-13 6-100-13 6-125-13	30.88 30.88 30.88	7.75 7.75 7.75	23.25 26.25 31.00	6-450B 6-600B 6-725B	6-450C 6-600C 6-725C
WP40/60/80 WRP60/80 32.00 x 13.50 x 31.00	24 24	600 750	12-100-13 12-125-13	30.88 30.88	12.88 12.88	26.25 31.00	12-600B 12-725B	12-600C 12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

BARRETT TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WEX40/60/HS/RT 32.00 x 8.13 x 31.00	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. WEX40/60 HS 32.00 x 13.25 x 31.00	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
WS30/40 34.50 x 8.25 x 31.00	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

UNICAR 140L 32.75 x 13.50 x 25.63	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
OPTIONAL COMP. 38.00 x 13.50 x 25.63	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 26" LEAD LENGTH, W/O COVER

Jun-98