

BIG JOE

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE, RIDER/WALKIES								
PDC15/20A 31.44 x 6.88 x OPEN	12	510	6-85-13	30.88	6.63	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	6.63	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	6.63	31.00	6-725B	6-725C
	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
	24	200	12-100-5	24.88	6.63	26.25	12-180A/B	N/A
PDC20/25/30/40 31.44 x 13.13 x OPEN	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	600	6-100-13	29.00	11.00	26.25	6-600B	6-600C
	12	1200	6-100-25	29.38	12.88	26.25	N/A	6-1200C
	12	750	6-125-13	29.00	11.00	31.00	6-725B	6-725C
	12	1500	6-125-25	29.38	12.88	31.00	N/A	6-1450C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
PDH20/25/30/40, PDP40, PDR20/30 31.63 x 6.88 x OPEN	12	510	6-85-13	30.88	6.63	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	6.63	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	6.63	31.00	6-725B	6-725C
	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
	24	200	12-100-5	24.88	6.63	26.25	12-180A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 15" LEAD LENGTH, W/ COVER

BIG-JOE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE, RIDER/WALKIES								
OPTIONAL COMP. PDH20/25/30/40, PDP40, PDR20/30 31.63 x 11.50 x OPEN	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
	12	600	6-100-13	29.00	11.00	26.25	6-600B	6-600C
	12	750	6-125-13	29.00	11.00	31.00	6-725B	6-725C
	24	340	12-85-9	29.25	10.25	23.25	6-380A/B	N/A
OPTIONAL COMP. 31.13 x 13.63 x OPEN	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	600	6-100-13	29.00	11.00	26.25	6-600B	6-600C
	12	1200	6-100-25	29.38	12.88	26.25	N/A	6-1200C
	12	750	6-125-13	29.00	11.00	31.00	6-725B	6-725C
	12	1500	6-125-25	29.38	12.88	31.00	N/A	6-1450C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
	WPT40/60, WRT40/60 31.50 x 6.88 x OPEN	12	510	6-85-13	30.88	6.63	23.25	6-450B
12		600	6-100-13	30.88	6.63	26.25	6-600B	6-600C
12		750	6-125-13	30.88	6.63	31.00	6-725B	6-725C
24		170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
24		200	12-100-5	24.88	6.63	26.25	12-180A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 15" LEAD LENGTH, W/ COVER

BIG-JOE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE, RIDER/WALKIES								
OPTIONAL COMP. WPT40/60, WRT40/60	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	600	6-100-13	29.00	11.00	26.25	6-600B	6-600C
	12	1200	6-100-25	29.38	12.88	26.25	N/A	6-1200C
	12	750	6-125-13	29.00	11.00	31.00	6-725B	6-725C
	12	1500	6-125-25	29.38	12.88	31.00	N/A	6-1450C
31.50 x 13.25 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 15" LEAD LENGTH, W/ COVER

STOCK SELECTORS								
SSC20	12	510	6-85-13	30.88	6.63	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	6.63	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	6.63	31.00	6-725B	6-725C
31.50 x 6.88 x OPEN	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
	24	200	12-100-5	24.88	6.63	26.25	12-180A/B	N/A
OPTIONAL SSC20 STANDARD SSC30 36.00 x 13.13 x OPEN	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C
	24	700	12-100-15	35.38	12.88	26.25	12-725B	12-725C
	24	875	12-125-15	35.25	13.00	31.00	12-875B	12-875C

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 15" LEAD LENGTH, W/ COVER

Jun-98