

# CLARK

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN RIDER								
EC500-20 33.50 x 25.00 x 23.00	36	595	18-85-15	31.75	24.00	22.63	18-600B	18-600C
	24	425	24-85-11	31.88	21.88	22.63	24-450B	24-450C
EC500-20/25/S30 33.50 x 26.75 x 23.00	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
	48	510	24-85-13	32.00	25.88	22.63	24-450B	24-450C
33.50 x 28.75 x 23.00	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	36	765	18-85-19	32.00	28.00	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
	48	510	24-85-13	32.00	25.88	22.63	24-450B	24-450C
EC500-25/S30 33.50 x 30.75 x 23.00	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	36	765	18-85-19	32.25	29.00	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
	48	595	24-85-15	32.25	29.75	22.63	24-600B	24-600C
EC500-60 39.50 x 32.00 x 23.75	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
EC500-60/70/80 39.50 x 37.00 x 23.75	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
	48	935	24-85-23	38.50	36.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>SIT-DOWN RIDER</b>								
EC500-60/70/80/22TLM/ 27TLM/33TLM/ ETL15/17/20 39.50 x 40.00 x 23.75	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
EC500-100 46.25 x 39.62 x 24.00	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1105	24-85-27	42.00	38.50	22.63	N/A	24-1050C
EC500-120 46.25 x 39.62 x 24.00	36	1530	(2)18-85-19				N/A	18-1450C
	48	1190	24-85-29	45.00	38.50	22.63	N/A	24-1200C
ECS10TLM/ETL10 38.90 x 34.50 x 23.15	36	765	18-85-19	38.50	33.63	22.63	18-725B	18-725C
	48	850	24-85-21	38.50	33.00	22.63	N/A	18-875C
TM12/15S 38.80 x 13.25 x 31.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
TM15/17/20/22/25 38.80 x 20.50 x 31.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

<b>STAND-UP RIDER</b>								
NST20/25/30/40 32.75 x 12.13 x 31.50	24	625	12-125-11	32.25	11.13	30.38	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-CD, 10" LEAD LENGTH, W/O COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>STAND-UP RIDER</b>								
NST20/25/30/40 32.75 x 16.63 x 31.50	24	750	12-125-13	30.88	12.88	30.38	12-725B	12-725C
37.00 x 12.13 x 31.50	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C
37.00 x 16.63 x 31.50	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
	24	875	12-125-15	36.13	14.25	30.38	N/A	12-875C

ABOVE REQUIRES: 175 GREY CONN., POSITION-CD, 10" LEAD LENGTH, W/O COVER

<b>NARROW AISLE REACH TRUCK</b>								
NP15/20 38.75 x 14.50 x 32.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
NP15/15D/20/22 38.75 x 16.50 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
38.75 x 21.00 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 20" LEAD LENGTH, W/O COVER

<b>NARROW AISLE REACH TRUCK</b>								
NP300-30/40/NS300-40/50 36.75 x 12.25 x 31.25	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 16" LEAD LENGTH, W/O COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>NARROW AISLE REACH TRUCK</b>								
NP300-30/40/NS300-40/50 36.75 x 14.50 x 31.25	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
36.75 x 16.50 x 31.25	24	875	12-125-15	36.13	14.25	30.38	N/A	12-875C
	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 16" LEAD LENGTH, W/O COVER

<b>NARROW AISLE ORDERPICKER</b>								
ETA 12 40.30 x 27.80 x 24.70	72	425	36-85-11	38.13	26.50	22.63	N/A	36-450C
ETA 15 40.30 x 39.10 x 24.70	72	680	36-85-17	40.00	38.50	22.63	N/A	36-725D

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

<b>NARROW AISLE ORDERPICKER</b>								
ETD10/15S 41.00 x 30.00 x 27.50	72	425	36-85-11	38.13	26.50	22.63	N/A	36-450C
	72	500	36-100-11	38.13	26.50	25.63	N/A	36-600C
ETD15 41.00 x 40.00 x 27.50	72	680	36-85-17	40.00	38.50	22.63	N/A	36-725D
	72	800	36-100-17	40.00	38.50	25.63	N/A	36-725D
ETR 10 33.00 x 25.10 x 25.40	24	850	12-85-21	32.63	19.25	22.63	N/A	12-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>NARROW AISLE ORDERPICKER</b>								
ETR13 41.00 x 30.00 x 27.50	72	800	36-100-17	40.00	38.50	25.63	N/A	36-725D

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

<b>NARROW AISLE ORDERPICKER</b>								
OP7 32.00 x 8.00 x 24.50	12	425	6-85-11	31.00	7.75	23.25	110V AUTO BUILT IN CHGR	
	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
32.00 x 13.50 x 24.50	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	24	425	12-85-11	31.50	12.88	23.25	110V AUTO BUILT IN CHGR	
	24	510	12-85-13	30.63	12.88	23.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>NARROW AISLE ORDERPICKER</b>								
OP15 36.50 x 13.63 x 31.50	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
39.25 x 13.88 x 31.50	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

<b>WALKIE-RIDER</b>								
HWD25/30/36/HWP25/30	24	255	12-85-7	33.88	6.63	23.25	12-255A/B	N/A
P25/30/PWD25/30/36	24	300	12-100-7	33.88	6.63	26.25	12-255A/B	N/A
35.50 x 7.00 x OPEN	24	375	12-125-7	33.75	6.56	31.00	12-380B	12-380C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>WALKIE-RIDER</b>								
HWD25/30/36/HWP25/30	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
P25/30/PWD25/30/36	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
31.40 x 13.60 x OPEN	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 28" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
P40/60	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
31.63 x 8.13 x OPEN	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
P40/60	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	1200	6-100-25	29.38	13.00	26.25	N/A	6-1200C
31.63 x 13.38 x OPEN	12	1500	6-125-25	29.38	13.00	31.00	N/A	6-1450C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
WP40  29.50 x 9.00 x OPEN	12	340	6-85-9	29.25	7.50	23.25	110V AUTO BUILT IN CHGR	
	12	375	6-85-11	26.38	7.75	23.25	6-380A/B	N/A
	12	500	6-100-11	26.50	7.75	26.25	6-450A	6-450B
	12	625	6-125-11	26.38	7.75	31.00	6-600B	6-600C
	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.69	26.25	12-255A/B	N/A
	24	375	12-125-7	25.50	8.63	31.00	12-380B	12-380C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>WALKIE-RIDER</b>								
S20/30/40/SP20/30 31.25 x 8.00 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
S20/30/40/SP20/30 31.25 x 13.44 x OPEN	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	1200	6-100-25	29.38	13.00	26.25	N/A	6-1200C
	12	1500	6-125-25	29.38	13.00	31.00	N/A	6-1450C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
ST20/30/40 32.00 x 14.63 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-275C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

<b>WALKIE-RIDER</b>								
ECS17/20/22/25/27/30 38.90 x 30.40 x 23.15	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
ECS17/20/22/25/27/30 38.90 x 34.40 x 23.15	36	1190	18-85-29	38.50	33.63	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
ECS17/20/22/25 38.90 x 27.50 x 23.15	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

**CLARK TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>WALKIE-RIDER</b>								
ESM12/15S 38.80 x 13.88 x 31.50	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
ESM15 38.80 x 16.13 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
ESM17 38.80 x 18.38 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
ESM20/22/25 38.80 x 20.75 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 12" LEAD LENGTH, W/O COVER

**Jun-98**