

# CROWN

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>STAND UP ELECTRIC</b>								
25RC 38.56 x 11.44 x 31.00	36	500	18-125-9	38.00	11.00	30.38	18-450B	18-450C
OPTIONAL 25RC STANDARD 30RC/ 38.56 x 13.68 x 31.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 12" LEAD LENGTH, W/O COVER

<b>SIT DOWN RIDER</b>								
40/50FC 38.69 x 27.25 x 22.75	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C
OPTIONAL 40/50FC STANDARD 60FC 38.69 x 33.00 x 22.75	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
OPTIONAL 50/60FC 38.69 x 36.00 x 22.75	36	1190	18-85-29	38.50	33.63	22.63	N/A	18-1200C
	36	1275	18-85-31	38.50	35.88	22.63	N/A	18-1200C

ABOVE REQUIRES: 350 GREY CONN. (36v), BLUE (48v), POSITION-A, 15" LEAD LENGTH, W/O COVER

<b>WALKIE</b>								
40GPW 25.63 x 8.82 x 24.00	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 20" LEAD LENGTH, W/COVER

**CROWN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
40/60/80PC/PE/PR/PW 35.06 x 6.62 x 23.25	24	255	12-85-7	33.88	6.63	23.25	12-255A/B	N/A
OPTIONAL COMP.  31.75 x 13.12 x OPEN	24	425	12-85-11	26.50	13.00	23.25	12-450B	12-450C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C

ABOVE REQUIRES: 175 GRY CONN., PC, PE, PW: POS-A, 20" LEAD LENGTH, PR: POS-A, 22" LEAD LENGTH, W/CVR

NARROW AISLE REACH								
35/45RR/RS 38.38 x 12.19 x 31.00	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	36	480	18-125-9	38.00	11.00	30.38	18-450B	18-450C
OPTIONAL RR/RS STANDARD RD 38.38 x 14.25 x 31.00	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL RR/RS/RD STANDARD RD45 38.38 x 16.25 x 31.00	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL RR45, RD30 38.69 x 20.75 x 31.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-A, 9" LEAD LENGTH, W/O CVR

25SC 38.62 x 15.88 x 23.12	36	510	18-85-13	38.38	15.50	22.63	18-450B	18-450C
-------------------------------	----	-----	----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 9" LEAD LENGTH, W/O COVER

**CROWN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
OPTIONAL 25SC STANDARD 30SC 38.62 x 18.38 x 23.12	36	595	18-85-15	38.50	17.75	22.63	18-600B	18-600C
OPTIONAL 30SC 38.62 x 20.62 x 23.12	36	680	18-85-17	38.00	19.88	22.63	18-725B	18-725C
OPTIONAL 30SC STANDARD 35SC 38.62 x 22.81 x 23.12	36	765	18-85-19	38.50	22.44	22.63	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 9" LEAD LENGTH, W/O COVER

NARROW AISLE STOCK								
15SP48, 30SP42/ 48 36.25 x 14.25 x 31.00	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C

ABOVE REQUIRES: 350 RED CONN., POSITION-A, 20" LEAD LENGTH, W/O COVER

NARROW AISLE STOCK								
30SP36 31.75 x 13.12 x 23.25	24	510	12-85-13	30.88	12.88	22.63	12-450B	12-450C

ABOVE REQUIRES: 175 GREY, POSITION-A, 17" LEAD LENGTH, W/O COVER

30SSR 36.38 x 11.75 x 31.00	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
--------------------------------	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 350 RED CONN., POSITION-A, 12" LEAD LENGTH, W/COVER

**CROWN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>TURRET SIDELoader/ STOCKPICKER</b>								
TS/TSP 38.38 x 13.62 x 31.00	72	625	18-125-11 (2) REQUIRED	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL COMP. 38.38 x 16.25 x 31.00	72	750	18-125-13 (2) REQUIRED	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.69 x 18.00 x 31.00	72	875	18-125-15 (2) REQUIRED	38.50	17.88	30.38	N/A	18-875C
TSP 38.75 x 27.00 x 31.00	48	1000	24-125-17	38.50	27.00	30.38	N/A	24-1050C
OPTIONAL COMP. 38.75 x 33.00 x 31.00	48	1250	24-125-21	38.50	33.00	30.38	N/A	24-1200D

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 9" LEAD LENGTH, W/O COVER

200TW, 140/200TWR 140/200/TR 35.06 x 6.63 x OPEN	24	255	12-85-7	33.88	6.63	23.25	12-255A/B	N/A
	24	300	12-100-7	33.88	6.63	26.25	12-380B	N/A
	24	375	12-125-7	33.75	6.56	31.00	12-380B	N/A
OPTIONAL COMP. 31.75 x 13.12 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 10" LEAD LENGTH, W/CVR

**CROWN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
W, WA, WB, WR, WTL WTF & WTT 35.06 x 6.62 x 23.25	24	255	12-85-7	33.88	6.63	23.25	12-255A/B	N/A
OPTIONAL COMP. 31.75 x 13.12 x 23.25	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., WB REQUIRES POS.-A, 10" LEAD LENGTH, W/COVER  
W, WA, WR, WTL, WTF, WTT REQUIRE POSITION-A, 17" LEAD LENGTH, W/COVER

**Jun-98**