

DREXEL

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				LGT	WD	HGT	(1) PHASE	(3) PHASE
FL-40/60EX 37.63 x 27.38 x OPEN	36	765	18-85-19EX	37.25	26.00	23.25	18-725B	18-725C

ABOVE REQUIRES: N-150-EX CONN., W/COVER; **EXPLOSION PROOF BATTERY REQUIRED**

SL-33-ESS 40.00 x 24.00 x 26.00	36	680	18-85-17	38.00	19.88	23.25	18-725B	18-725C
	36	765	18-85-19	38.50	22.44	23.25	18-725B	18-725C
SL-33-ESS-HP 40.00 x 26.38 x 26.00	36	850	18-85-21	38.50	24.50	23.25	N/A	18-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/COVER

SL-44/55-ESS 39.25 x 30.88 x 23.75	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
SL-44-ESS-HP 39.25 x 37.38 x 23.75	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
SL-66-ESS 39.25 x 37.38 x 23.75	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
OPTIONAL SL-66-ESS STANDARD SL-77/88-ESS 40.50 x 37.38 x 23.75	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

Jun-98