

HYSTER

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
A30XL 32.90 x 19.60 x 26.60	24 24	850 1000	12-85-21 12-100-21	32.63 32.5	19.25 19.31	22.63 25.38	N/A N/A	12-875C 12-1050C

ABOVE REQUIRES: 350 RED CONN., POSITION-A, 9" LEAD LENGTH, W/O COVER

WALKIE/RIDER, CENTER RIDER								
B60/80XT, C60/80XT 32.00 x 13.40 x 28.84	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
OPTIONAL B60/80XT 32.00 x 9.00 x 28.84	24	300	12-100-7	25.50	8.75	26.25	12-255A/B	N/A

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

STAND-UP END CONTROL								
E30ER 38.69 x 16.00 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
E40/50ER 38.69 x 20.75 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 8" LEAD LENGTH, W/O COVER, DISCONNECT HANDLE REQUIRED

E30FR-24 38.75 x 15.50 x 31.62	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
-----------------------------------	----	------	-----------	-------	-------	-------	-----	----------

ABOVE REQUIRE: 350 RED CONN., POSITION-D, 9" LEAD LENGTH, W/O COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
E30-35FR 38.75 x 16.12 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
E40-50FR 38.88 x 20.60 x 31.62	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 9" LEAD LENGTH, W/O COVER

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
E40/50/55XL TRUCK WITH HOOD 38.86 x 27.32 x 23.15	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C
TRUCK W/O HOOD 38.86 x 27.32 x 24.29	36	935	18-85-23	38.50	26.75	23.25	N/A	18-875C
	48	680	24-85-17	38.50	27.00	23.25	N/A	24-725C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 20" LEAD LENGTH, DISCONNECT HANDLE REQUIRED
BATTERIES IN TRUCK WITH HOOD-W/O COVER, BATTERIES IN TRUCK W/O HOOD-W/COVER

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
OPTIONAL E40/50/55/ 60XL TRUCK W/O HOOD 38.88 x 33.11 x 24.29	36	1105	18-85-27	38.50	31.38	23.25	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	23.25	N/A	24-875C
STANDARD E60XL TRUCK WITH HOOD 38.86 x 33.11 x 23.15	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, DISCONNECT HANDLE REQUIRED
BATTERIES IN TRUCK WITH HOOD-W/O COVER, BATTERIES IN TRUCK W/O HOOD-W/COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
E100/120XL TRUCK WITH HOOD 44.10 x 45.70 x 23.15	36	1530	(2)18-85-19 24-85-33	38.50	44.88	22.63	N/A	18-1450C
	48	1360		SEE FACTORY				
TRUCK W/O HOOD 45.00 x 45.70 x 24.29	36	1530	(2)18-85-19 24-85-33	38.50	44.88	23.25	N/A	18-1450C
	48	1360		SEE FACTORY				

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 20" LEAD LENGTH, DISCONNECT HANDLE REQUIRED
BATTERIES IN TRUCK WITH HOOD-W/O COVER, BATTERIES IN TRUCK W/O HOOD-W/COVER

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
E100XLS TRUCK WITH HOOD 44.10 x 39.20 x 23.15	36	1360	18-85-33 24-85-27	38.50	38.13	22.63	N/A	18-1450C
	48	1105		42.00	38.50	22.63	N/A	24-1050C
TRUCK W/O HOOD 45.00 x 39.20 x 24.29	36	1360	18-85-33 24-85-27	38.50	38.13	23.25	N/A	18-1450C
	48	1105		42.00	38.50	23.25	N/A	24-1050C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, DISCONNECT HANDLE REQUIRED
BATTERIES IN TRUCK WITH HOOD-W/O COVER, BATTERIES IN TRUCK W/O HOOD-W/COVER

E25-35XL ₂ TRUCK WITH HOOD 35.16 x 27.32 x 23.15	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	18-450B	18-450C
TRUCK W/O HOOD 35.79 x 27.32 x 24.57	36	765	18-85-19	35.25	25.75	23.25	18-725B	18-725C
	48	595	24-85-15	35.50	26	23.25	18-600B	18-600C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 29" LEAD LENGTH, DISCONNECT HANDLE REQUIRED
BATTERIES IN TRUCK WITH HOOD-W/O COVER, BATTERIES IN TRUCK W/O HOOD-W/COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
E25-35XM, E40XMS 34.57 x 27.36 x 24.13	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 30" LEAD LENGTH, W/O COVER

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
E45/50XM 38.86 x 27.36 x 24.41	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	24-600B	24-600C
E55/60XM 38.86 x 33.15 x 24.41	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
E65XM 38.86 x 39.76 x 24.41	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	935	24-85-23	38.50	36.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER,
DISCONNECT HANDLE REQUIRED

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
J40/50XL TRUCK WITH HOOD 38.86 x 33.15 x 23.15	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
TRUCK W/O HOOD 38.86 x 33.15 x 24.57	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER,
DISCONNECT HANDLE REQUIRED

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
STANDARD J60XL OPTIONAL J40/50XL TRUCK WITH HOOD 38.86 x 39.76 x 23.15	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
TRUCK W/O HOOD 38.86 x 39.76 x 24.57	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
J30XMT 39.00 x 16.70 x 23.10	36	510	18-85-13	38.38	15.50	22.63	18-450B	18-450C
	48	340	24-85-9	38.50	14.63	22.63	18-380B	18-380C
OPTIONAL COMP. 39.00 x 16.70 x 26.10	36	600	18-100-13	38.38	15.88	25.63	18-600B	18-600C
	48	400	24-100-9	38.50	14.63	25.63	24-380B	24-380C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER,
DISCONNECT HANDLE REQUIRED

SIT-DOWN COUNTER BALANCE (FOUR WHEEL)									
J40/50XM 40.70 x 28.22 x 31.70	36	1375	18-125-23	38.50	27.25	30.38	N/A	18-1450C	
	48	1000	24-125-17	38.50	27.00	30.38	N/A	24-1050C	
STANDARD J60XM OPTIONAL J40/50XM 40.70 x 33.98 x 31.70	36	1500	18-125-25	SEE FACTORY					
	48	1250	24-125-21	38.50	33.00	30.38	N/A	24-1200C	
J35/40XMT 39.00 x 25.20 x 23.10	36	850	18-85-21	38.50	24.50	22.63	N/A	18-875C	
	48	595	24-85-15	38.50	24.00	22.63	24-600B	24-600C	

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 20" LEAD LENGTH, W/O COVER,
DISCONNECT HANDLE REQUIRED

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN COUNTER BALANCE (FOUR WHEEL)								
J35/40XMT OPTIONAL COMP. 39.00 x 25.20 x 26.10	36	1000	18-100-21	38.50	24.63	25.63	N/A	18-1050C
	48	700	24-100-15	38.25	23.75	25.63	N/A	24-725C

ABOVE REQUIRES: 350 GREY (36v), BLUE (48v), POSITION-A, 20" LEAD LENGTH, W/O COVER, DISCONNECT HANDLE REQUIRED

MAN-DOWN								
N30AH TRUCK WITH HOOD 38.86 x 39.76 x 23.15	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
TRUCK W/O HOOD 38.86 x 39.76 x 24.57	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C

ABOVE REQUIRES: 350 RED CONN., POSITION-B, 16" LEAD LENGTH, W/O COVER

REACH TRUCKS								
N30FR 39.00 x 12.50 x 31.50	24	875	12-125-15	38.25	12.00	30.30	N/A	12-875C
OPTIONAL COMP. 39.00 x 14.60 x 31.50	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
N40FR, N50FA 39.00 x 14.60 x 31.50	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL COMP. 39.00 x 16.60 x 31.50	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 RED (24v), GREY (36v), POSITION-B, 16" LEAD LENGTH, W/O COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
REACH TRUCKS								
N45FR 39.00 x 16.60 x 31.50	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1050C
OPTIONAL COMP. 39.00 x 18.75 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
OPTIONAL COMP. 39.00 x 21.12 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 RED (24v), GREY (36v), POSITION-B, 16" LEAD LENGTH, W/O COVER

RACKLOADER								
R30CH 39.00 x 23.80 x 31.50	36 36	1000 1125	18-125-17 18-125-19	38.50 38.50	20.13 22.38	31.00 31.00	N/A N/A	18-1050C 18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

RACKLOADER								
R40EH 42.40 x 17.40 x 31.50	72	750	(2)18-125-13	38.00	15.50	30.38	N/A	36-725D

ABOVE REQUIRES: SBX350 GREY CONN., POSITION-A, 40" LEAD LENGTH, W/O COVER

ORDERPICKER TRUCKS								
R30ES 36.00 x 13.50 x 24.71	24	595	12-85-15	35.38	13.00	22.63	12-600B	12-600C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 16" LEAD LENGTH, W/O COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ORDERPICKER TRUCKS								
R30F, R30FA, R30FF 39.00 x 14.60 x 31.50	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 RED (24v), GREY (36v), POSITION-B, 20" LEAD LENGTH, W/O COVER

STRADDLE STACKER								
W20/30XTA 35.40 x 8.12 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
	24	255	12-85-7	33.88	7.75	23.25	12-255A/B	N/A
	24	300	12-100-7	33.88	6.63	26.25	12-255A/B	N/A
	24	375	12-125-7	33.75	6.56	31.00	12-380B	12-380C
STANDARD W40XTA, W20/30XTR OPTIONAL W20/30XTA 35.40 x 13.50 x OPEN	12	765	6-85-19	31.25	13.13	23.25	6-725B	6-725C
	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C

MINIMUM BATTERY WEIGHT - 400#, MAXIMUM BATTERY WEIGHT - 1100#

COUNTERBALANCED STACKERS								
W20/25/30/40XTC 31.87 x 13.38 x OPEN	12	765	6-85-19	31.25	13.13	23.25	6-725B	6-725C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

MINIMUM BATTERY WEIGHT - 400#, MAXIMUM BATTERY WEIGHT - 1400#

PALLET TRUCK								
W40XT 28.75 x 7.80 x 24.30	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
PALLET TRUCK								
W40XT OPTIONAL COMP. 25.75 x 6.88 x OPEN	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
	24	200	12-100-5	24.88	6.63	26.25	12-180A/B	N/A
OPTIONAL COMP. 29.50 x 7.80 x 25.40	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

WALKIES								
W40/60XL, 40/60XL 31.90 x 8.30 x 23.90	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
OPTIONAL COMP. 31.90 x 13.60 x 23.90	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C

ABOVE REQUIRES: 175 YELLOW (12v), RED (24v), POSITION-B, 15" LEAD LENGTH, W/COVER

WALKIES								
W45XT 31.75 x 8.10 x 28.84	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C

ABOVE REQUIRES: 175 YELLOW CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

WALKIES								
STANDARD W60XT	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
OPTIONAL B60/60XT,	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
W80XT	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
32.00 x 9.00 x OPEN	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.75	26.25	12-255A/B	N/A

ABOVE REQUIRES: 175 YELLOW CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

HYSTER TRUCKS CONTINUED

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				LGT	WD	HGT	(1) PHASE	(3) PHASE
WALKIES, RIDERS, TOW TRACTORS								
OPTIONAL W60XT	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
STANDARD W80XT,	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
B60/80XT, C60/80XT,	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
T5XT	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
32.00 x 13.40 x 31.00								

ABOVE REQUIRES: 175 YELLOW (12v), RED (24v), POSITION-B, 20" LEAD LENGTH, W/COVER

Jun-98