

# MITSUBISHI

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>NARROW AISLE</b>								
EOP15-24 31.50 x 13.25 x 32.25	24	750	12-125-13	30.88	12.88	30.38	12-725B	12-725C
EOP15-24P 36.75 x 14.50 x 32.25	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C

ABOVE REQUIRES: 350 RED CONN., POSITION-C, 12" LEAD LENGTH, W/O COVER

<b>DOUBLE/SINGLE REACH, STRADDLE STACKER</b>								
EDR/SR/SS-24 38.67 x 14.25 x 31.62	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
EDR/SR/SS-36 38.67 x 16.25 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-B, 11" LEAD LENGTH, W/O COVER

<b>SIT-DOWN RIDER, CUSHION TIRE</b>								
FBC15/18 35.80 x 27.80 x 23.30	36	765	18-85-19	35.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.50	26.00	22.63	24-600B	24-600C
FBC20/25 39.90 x 30.50 x 23.30	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	24-725B	24-725C
FBC25E/30 39.90 x 34.40 x 23.30	36	1190	18-85-29	38.50	34.00	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

**MITSUBISHI TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>STAND UP COUNTERBALANCED REACH</b>								
FBR13/W13 38.00 x 13.40 x 23.5	24	595	12-85-15	35.38	13.00	22.63	12-600B	12-600C
FBR15/W/15/18/W18 37.80 x 18.70 x 23.5	48	425	24-85-11	37.75	18.00	22.63	24-450B	24-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-D, 15-18" LEAD LENGTH, W/O COVER

<b>SIT-DOWN RIDER, THREE WHEEL</b>								
FBS15 39.20 x 20.60 x 24.40	36	680	18-85-17	38.00	19.88	22.63	18-725B	18-725C
	48	510	24-85-13	38.13	20.63	22.63	24-450B	24-450C
FBS18/20 39.20 x 24.90 x 24.40	36	850	18-85-21	38.50	24.50	22.63	N/A	18-875C
	48	595	24-85-15	38.50	24.00	22.63	24-600B	24-600C
FET10/13 39.30 x 16.10 x 25.50	36	600	18-100-13	38.00	15.50	25.63	18-600B	18-600C
FET15/18 39.30 x 22.80 x 25.50	36	800	18-100-17	38.50	20.13	25.63	N/A	18-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

<b>NARROW AISLE REACH</b>								
FER15C/15D FER20C/20D 38.50 x 16.60 x 32.60	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN. (24v), RED (36v), POSITION-C, 15-18" LEAD LENGTH, W/O COVER

**MITSUBISHI TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER (1) PHASE	CHARGER (3) PHASE
				X	Y	Z		
<b>TOW TRACTOR</b>								
NTT90T 32.00 x 13.30 x 23.40	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
NTT90TA 32.00 x 13.30 x 23.40	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

<b>LOW-LIFT PALLET TRUCK</b>								
PLDM20/20A/20B/ 30/30A/30B 32.00 x 8.10 x 23.50	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
PLDM20/20A/20B/ 30/30A/30B 32.00 x 13.30 x 23.50	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
PMW20 29.38 x 8.88 x 26.5	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

<b>LOW-LIFT PALLET TRUCK</b>								
PMW30 32.00 x 9.19 x 24.00	24	255	12-85-7	31.00	8.63	23.25	12-255A/B	N/A
OPTIONAL COMP. 32.00 x 13.44 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

**MITSUBISHI TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>LOW-LIFT PALLET TRUCK</b>								
PMCR/WR30 32.00 x 13.44 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
31.50 x 13.44 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
PMCR/WR40, PMT90 31.50 x 13.44 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

**Jun-98**