

# NISSAN

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
DG 31.75 x 13.125 x 23.50	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH W/COVER

E20Y	36	595	18-85-15	31.75	24.00	22.63	18-600B	18-600C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
E25/30/35Y 35.20 x 26.70 x 23.40	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 14" LEAD LENGTH, W/O COVER

E40/50Y 39.10 x 28.30 x 23.40	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C
E50L/E55/60Y 39.10 x 34.20 x 23.40	36	1190	18-85-29	38.50	33.63	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

EWP 28.25 x 9.00 x 24.00	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
-----------------------------	----	-----	---------	-------	------	-------	-----------	-----

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

N30/35 39.20 x 20.90 x 25.80	48	425	24-85-11	37.75	18.00	22.63	24-450B	24-450C
	48	510	24-85-13	38.13	20.63	22.63	24-450B	24-450C
	48	600	24-100-13	38.13	20.63	25.63	24-600B	24-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

**NISSAN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
OR35/40 38.75 x 13.88 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL OR35/40/45 38.75 x 16.13 x 32.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OR45 38.75 x 18.50 x 32.00	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
OPTIONAL COMP. 38.75 x 21.00 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C
ORB35/ 40 38.75 x 13.88 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL ORB35/40/45 38.75 x 16.13 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
ORB45 38.75 x 18.50 x 32.00	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
OPTIONAL ORB45 38.75 x 21.00 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C
OS25/30S 38.80 x 13.88 x 31.50	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

**NISSAN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
OS30 38.80 x 16.13 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OS35 38.80 x 18.38 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
OSB25/30S 38.80 x 13.88 x 31.50	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OSB30 38.80 x 16.13 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OSB35 38.80 x 18.38 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
OT25/30S 38.80 x 13.75 x 31.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OT30/35/40/45/50 38.80 x 20.50 x 31.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 20" LEAD LENGTH, W/O COVER

PE30/35Y 35.16 x 26.69 x 23.43	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.00	25.88	22.63	24-600B	24-600C
PE40/50Y 39.09 x 28.27 x 23.43	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C

**NISSAN TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
PE50LY/60Y 39.09 x 34.17 x 23.43	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

RCOS3000 38.75 x 14.50 x 31.50	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

WP/WS/WTT 32.00 x 8.25 x 31.00	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
-----------------------------------	----	-----	----------	-------	------	-------	--------	--------

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

OPTIONAL WP/WS/WTT STANDARD SG/SGX/WRF 32.00 x 13.50 x 31.00	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

Jun-98